

Smart Life App



PC4713 Tuya Series Smart Energy Meter

Quick Start Guide


Safety Handling

WARNING: Failure to follow these safety notices could result in fire, electric shock, other injuries, or damage to the relay and other property. Read all the safety notices below before using the relay.

- Avoid high humidity or extreme temperatures.
- Avoid long exposure to direct sunlight or strong ultraviolet light.
- Do not drop or expose the unit to intense vibration.
- Do not disassemble or try to repair the unit yourself.
- Do not expose the unit or its accessories to flammable liquids, gases or other explosives.

1

Welcome



PC4713 Tuya series smart energy meter helps you monitor the amount of electricity Consumed and Produced in your three-phase power system by connecting the clamps on to the power cables. It is also compatible with split-phase and single-phase. It allows you to check real-time or historical energy data via mobile App.

This product series includes 4 variants with different communication and relay configurations. All variants share identical metering core, measurement accuracy, housing dimension and power supply parameters. Differences only exist in Ethernet port and built-in relay output function, as listed below:

Model Name	Wi-Fi	Ethernet Port	Built-in Relay Output
PC4713-W-E-TY/R	✓	✓	✓
PC4713-W-E-TY	✓	✓	X
PC4713-W-TY/R	✓	X	✓
PC4713-W-TY	✓	X	X

Main Features:

- Tuya compliant. Support automation with other Tuya device by export and import of grid or other energy values
- Three-Phase, Split-Phase and Single-Phase electricity system compatible
- Remotely monitor whole home Energy with three current transformers
- Wireless communication via Wi-Fi 2.4GHz
- Real-time Voltage, Current, PowerFactor, Frequency, ActivePower, ReactivePower, ApparentPower measurement
- Bidirectional measurement: Energy Usage / Solar Production
- Historical data could be displayed and exported in App
- Ethernet helps you improve the Network stability (optional)
- Dry contact relay, resistive current rated 3A, max. 5A, overload protection and relay setting (optional)

Technical Specifications

Connectivity

Wi-Fi • 802.11 b/g/n @2.4GHz

BLE • For Pairing

Ethernet (Optional) • 10/100 Mbps

Physical Specifications

Operating Voltage (RMS for each phase) • 90~277 Vac 50/60 Hz


Supported Systems • Single-Phase
• Split-Phase
• Three-Phase (3-Phase 3-Wire & Delta system are not supported)

Power Consumption • < 2W

Voltmeters Accuracy • $\pm 1\%$


Ammeters Accuracy • 80A CT: $\pm 1\%$ (1-80A) , $\pm 2\%$ (0-1A)
• 120A CT: $\pm 1\%$ (2-120A) , $\pm 2\%$ (0-2A)
• 200A CT: $\pm 1\%$ (2-200A) , $\pm 2\%$ (0-2A)
• 300A CT: $\pm 1\%$ (6-300A) , $\pm 2\%$ (2-6A) ,
 $\pm 5\%$ (0-2A)
• 500A CT: $\pm 1\%$ (6-500A) , $\pm 2\%$ (2-6A) ,
 $\pm 5\%$ (0-2A)
• 750A CT: $\pm 1\%$ (6-750A) , $\pm 2\%$ (2-6A) ,
 $\pm 5\%$ (0-2A)

Clamp Inner Dimension	• 80A (default): Ø10mm • 120A(optional): Ø16mm • 200A(optional): Ø20mm • 300A(optional): Ø24mm • 500A(optional): Ø36mm • 750A(optional): Ø51mm
Relay Type (Optional)	• Dry contact relay, resistive current rated 3A, max. 5A
Reporting Cycle	• Energy data: every 15 seconds • Relay status: immediately (Relay Version)
Operating Environment	• Temperature: -20°C ~ +55°C • Humidity: ≤ 90% non-condensing
Mount Type	• 35mm DIN rail mounting
Dimension	• 19 (W) x 69(D) x 90 (H) mm



2

Get to know your device



Reset Button

- Press 1 time to switch the relay On/Off (Relay version, can be set in APP)
- Press 3 times quickly to reboot the device
- Press and hold for 5 sec to reset the network
- Press and hold for 10 sec to factory reset

LED Indication

LED	Behavior	Status
Power	On	Power Supply is connected
	Slow Blink	Phase sequence error warning
	Fast Blink 1 times	Ready to reboot
	Fast Blink 2 times	Ready to reset network
	Fast Blink 3 times	Ready to factory reset
Net	On	Connected TUYA Cloud
	Slow Blink	AP mode, wait for configuring
	Medium Blink	STA mode, but failed to connect router
	Fast Blink	STA mode, connected router, but failed to connect TUYA Cloud
Out (Relay version)	On	Relay in on
	Off	Relay is off

Note: Fast Blink: 200ms ON / 200ms OFF
 Medium Blink: 500ms ON / 500ms OFF
 Slow Blink: 1500ms ON / 1500ms OFF

3

Wiring

1) Before installation, please turn off the circuit breakers of the distribution box and make sure there is no voltage on their terminals.

2) Mount the main unit of energy meter onto the DIN rail.

3) According to the below wiring diagrams to install. Taking a three-phase four-wire wiring as an example.

3.1 Use four power cords to connect the Power Terminal A/B/C/N in parallel to the L1/L2/L3/N lines at the output of the circuit breaker respectively.

3.2 Plug the power cord of CT1 into the IA port of CT Terminal, connect the "+" wire to "IA+", and connect the "-" wire to "IA-". Similarly, connect CT2 to the IB port and CT3 to the IC port.


3.3 Put CT1/CT2/CT3 around the cables L1/L2/L3 respectively, with the arrow direction pointing towards the loads.

3.4 Insert the Power Terminal and CT Terminal into the corresponding positions on the main unit.


4) After confirming that all connections are correct, turn on the circuit breakers

Scan code to watch the installation video

Three Phase
Four Wire,
Wiring




Split Phase,
Wiring




Scan code to watch the installation video

Single Phase,
Three Loads
Wiring



Single Phase,
One Circuit
Wiring



Note: Please ensure that the power supply wiring of the device and the corresponding CT measurement circuit are on the same phase

4 Configure Network


Download APP

Download the "Smart Life" app from the App Store. You can also scan the QR code below to download and install it.



Method 1:

1. Open Smart Life APP and click the "Scan" button in the upper right corner of the APP Home page.



2. Scan the following QR code to configure the network



PC4713-W-E-TY/R



PC4713-W-E-TY




PC4713-W-TY/R



PC4713-W-TY

Method 2:

1. Turn on your phone's Bluetooth and open the "Smart Life" app. Then tap "Add Device" to enter the configuration page. The app will automatically scan for nearby devices.



3. Select the found device and tap to pair it with the network. If you are adding the device via Wi-Fi, you will need to enter the Wi-Fi name and password. If you are adding the device via Ethernet, you will need to plug in an Ethernet cable that can connect to the internet.

Note: Please make sure the Wi-Fi you are connecting is **2.4GHz**. If no device is detected, try to press and hold the **Reset** button for 5 seconds, ensuring the **Net** Led blinks slowly, then try again.