




Products

– Control & Lightings

SLC628

In-Wall Switch



Description

The In-wall Touch Switch allows you to remotely control your lighting or even apply schedules for automatic switching from the mobile app.

Main Features

- ZigBee 3.0 compliant
- Works with any standard ZigBee Hub
- Remote on/off control using your smartphone
- Set schedules to automatically power on and off as needed
- 1/2/3 gang is available for selection

Main Specifications

Wireless Connectivity	
ZigBee	• 2.4GHz IEEE 802.15.4
ZigBee Profile	• ZigBee 3.0
RF Characteristics	• Operating frequency: 2.4GHz • Range outdoor/indoor: 100m / 30m • Internal PCB Antenna
Physical Specifications	
Button	• Touch Screen
Operating Voltage	• 100~240 Vac 50/60 Hz
Power consumption	• < 1 W
Max. Load Current	Each gang: • < 700W Resistive • < 200W Inductive
Operating environment	• Temperature: -20 °C ~+55 °C • Humidity: ≤ 90% non-condensing
Dimension	CN standard: • 89.2 x 89.2mm • In-wall size: 67.5x 61.1 x 26.2mm EU standard: • 89.2 x 89.2mm • In-wall size: 62.8x 62.8 x 26.5 mm
Weight	• 114 g
Mounting Type	• In- wall mounting • EU standard or CN standard
Certificate	• EU: ROHS • CN: CE, ROHS